



UNISTEP CARE OIL

Unistep Care Oil is oxidative hardening indoor maintenance oil for periodic maintenance and heavy cleaning of all Unistep oiled wood and parquet floors. Unistep Care Oil maintenance can be used over 1-component natural Unistep Oil, as a protective coating when the Unistep Oil is first applied. This will increase the resistance of Unistep Oil to dirt and water over the initial period of use. Care Oil conserves, cleans and improves floors treated with one-component natural oil, hardwax oil and two-component oil systems. An oiled surface requires a maintenance treatment with Care Oil when it has got a grey or dirty look which no longer can be refreshed by regular cleaning. Care Oil dries fast and has exceptionally good coverage. The solvents used in Care Oil require no warning labels.

DIRECTIONS FOR USE

Before using maintenance oil the surface has to be cleared of all loose particles which could otherwise damage the floor. Protect the floor from direct sunlight and keep off all underfloor heating from day before application till 24 hours after application. The temperature of the floor, oil and air must be between 13°C (55°F) and 25°C (77°F). Relative humidity of the room should be between 40% and 60%. Higher humidity of room extends drying time of finish thus waiting time between layers. At high temperatures and low relative humidity add 2% "Extender". Shake the container before use for 30-60 seconds. Do not dilute the oil. For application of Unistep Care Oil maintenance we recommend high quality red and white pads.

APPLICATION

Maintenance procedure for slightly soiled floors: Apply Unistep Care Oil maintenance oil sparingly on the surface and work it into the wood with a cotton cloth or a buffer with a white pad. Continue buffing until the floor appears to be saturated and no more drops or smears are visible. Work systematically on an area of 10-15 m² at a time, and ensure the overlaps are buffed carefully. Replace dirty cloths or pads as required. Allow a minimum of 3 hours drying time before use, preferably leave overnight. Do not use the floor during this period.

Maintenance procedure for heavily soiled floors: Apply Unistep Care Oil maintenance oil generously and work it into the wood with a red pad. If the red pad does not give the desired effect, gradually increase the abrasion level of the pads. Clean off the dirty oil completely. When the floor appears to be clean and saturated, apply a new thin layer of Unistep Care Oil maintenance, and buff with a white pad until no more drops or smears appear. Allow a minimum of 8 hours drying time before use, preferably leave overnight. Do not use the floor during this period.

TECHNICAL DATA

Content: Urethane modified pinewood oil, solvent Paraffin.

Recommended Use: For maintenance and heavy cleaning of all oiled surfaces

Gloss Levels: The gloss level can be adjusted by buffing.

VOC: 616 g /l (EU limit value for this product (cat. A/f): 700 g/l (2010) 2004/42/CE)

Solids by Volume: 38%

Odour: Very light, non-offending

Safety/Toxicity: Non-hazardous / Not classified

Coverage: 1 litre for 40-80 m² , depending on wood species and wood condition.

Flow and Leveling: Exceptional

Color Wet: milky white, clear when dry

Drying Time: 20°C/ 68°F (RH 50%) 3 - 8 hours after buffing.

Packaging: 5 l metal can. 1 l metal can.

Storage and transport: Best before 2 years after production at max 40°C in unopened can. Once the can is opened the content might start hardening. Store upside down. Not sensitive to frost.

Shelf life: See expiration date on canister.

Chemical Resistance: Resistant to grease, water and ordinary household cleaners and detergents.

Cleaning of tools: Thoroughly clean all application tools with water, right after using. Store used materials in water or in closed containers. The trowel and other tools can be cleaned with white spirit before the oil has hardened.

Disposal: Dispose it in accordance to local regulations.

Maintenance: Dry cleaning is recommended on all oiled surfaces. If necessary clean with Unistep Cleaner. Do not leave water on the floor. If the floor is heavily worn, maintain with Unistep Care Oil. If this does not give the desired result, sand lightly with a sanding screen grit 120 and apply a fresh layer of Unistep Oil.

NOTE! Oil saturated cloths and pads can self-ignite. Store used materials in water or in closed containers.

There are no express or implied warranties, including warranties of merchantability and/or fitness for a particular purpose. Buyers remedies are limited to replacement or refund of the purchase price. Manufacturer assumes no liability for injuries, incidental or consequential damages. User shall determine suitability of product for intended use. The information and recommendations in this data sheet are guidelines for application and are not to be construed as a guarantee. In all cases it is the responsibility of the user to determine if the product is suitable for the purpose, and complete a successful application. Unistep can only guarantee the delivered product. If the user is in doubt we would recommend a preliminary onsite test. Please ensure you have read and understood all information on the labels and in the safety data sheets before using.





UNISTEP CLEANER

Unistep Cleaner is a neutral cleaning product specially formulated for oiled and lacquered wooden floors. The neutral and non-toxic formula works well on all washable surfaces such as wood, PVC, linoleum, vinyl, other oiled/lacquered surfaces, stone, laminate, tiles, glass, porcelain etc. Cleaner contains no organic solvents or pigments and is environmentally friendly.

CLEANING OF ALL KINDS OF FLOORS

Before using Cleaner remove all loose particles which might scratch the surface during vacuuming or dry sweeping the floor. Dilute Cleaner according to instructions below. Especially on oiled floor the water temperature has to be observed. Refill the Cleaner Spray bottle or Spray Mop tank with suitable diluted Cleaner mix.

Spray the mixture and wipe the floor with damp mop. Flush and squeeze the mop in water regularly. Remove excess water from the mop before spraying Cleaner on the floor. Rinsing after cleaning is not necessary. Cleaner dries fast without leaving any streaks or haze. It is safe for your children and pets.

After every fifth wet cleaning with Spray Cleaner, the floor should be treated with Unistep Soap floor soap (blended in cold water, max 20°C) to refresh the oiled surface. Effects of wear and tear can be prevented and the floor can be maintained using Unistep Care Oil.

NOTE! Never pour water directly onto wood or laminate floors, instead use a damp cloth or floor mop and remove excess water immediately.

TECHNICAL DATA

Oiled floors: 1:200; 5ml/1l water (20°C)

Lacquered floors: 1:100; 10ml/1l water (30°C)

Heavy cleaning of lacquered floors: 1:20; 50ml/1l water (30°C)

Use in buffing machine: 1:200; 50ml/10l water (max 20°C)

VOC: 0 g /l (EU limit value for this product (cat. A/i): 140 g/l (2010) 2004/42/CE)

Content: Ethoxylated hydrocarbons

pH: 7

Recommended Use: For maintenance and cleaning of different floor types.

Odour: Very light, non-offending

Drying time: Ca 15 minutes (20°C/ 68°F, RH 50%)

Safety/Toxicity: Non-hazardous / Not classified

Packaging: 6x1 liter (Concentrate).

Storage and transport: Best before 5 years in unopened container from date of production.

Store on temperatures between 5°C (41°F) and 25°C (77°F). Protect from frost!

Shelf life: See expiration date on canister.

Cleaning of tools: Flush and squeeze the mop regularly. Clean tools in water after use.

Disposal: Dispose it in accordance to local regulations.

Maintenance: Dry cleaning is recommended on all oiled surfaces. If necessary clean with Unistep Cleaner. Do not leave water on the floor. If the floor is heavily worn, maintain with Unistep Care Oil.

There are no express or implied warranties, including warranties of merchantability and/or fitness for a particular purpose. Buyers remedies are limited to replacement or refund of the purchase price. Manufacturer assumes no liability for injuries, incidental or consequential damages. User shall determine suitability of product for intended use. The information and recommendations in this data sheet are guidelines for application and are not to be construed as a guarantee. In all cases it is the responsibility of the user to determine if the product is suitable for the purpose, and complete a successful application. Unistep can only guarantee the delivered product. If the user is in doubt we would recommend a preliminary onsite test. Please ensure you have read and understood all information on the labels and in the safety data sheets before using this product. This data sheet replaces all previous versions.





UNISTEP REMOVER

Unistep Remover is a heavy floor cleaner, specially formulated for removal of polish and wax. Unistep Remover dissolves water, oil, ethanol- and alkalinesoluble patches, and effectively removes rubber heel marks.

APPLICATION

Remove any dirt and debris that may scratch the surface. Apply an even coat using a cloth or a mop. When removing polish, leave on remover for a few minutes before scrubbing and properly rinsing with water (neutralization). Note: Rinse out all traces of the remover, since any residue may interfere with polishing. Use a fiber brush or red (or black) disk pad when using a machine buffer. Be very careful when cleaning oak parquet floors since discoloration may occur. Always follow the recommended dosage. Do not soak wooden floors, remove water immediately. The floor must be completely dry before screening and recoating. For clean-up use water to clean cloth and other tools.

HEALTH AND ENVIRONMENT

Unistep Remover is not classified as hazardous to your health or the environment. Irritant to eyes and skin. Keep out of the reach of children. In case of eye contact, immediately flush with water and seek medical advice. For skin, immediately wash with plenty of water. Precautions common for handling chemical products should be taken. Provide adequate ventilation. Use protective goggles and gloves when risk of splashing. For further information, please refer to the Material safety data sheet.

TECHNICAL DATA

Contents: Non-ionic surfactants: 1-5 %, complexing and alkaline agents

pH: Approx 11

Recommended Dosage: Heavy duty cleaning: 50 - 100 ml/10 l water, Polish removal: 500 - 1000 ml/10 l water, Polish removal Oak: 100 - 500 ml/10 l water

Shelf life: 36 months in unopened container. Store free of frost. Keep out of children's reach.

Packaging: 1 l

The information and recommendations in this publication are the best of our knowledge, information and belief accurate at the date of publication. Nothing herein is to be construed as warranty, express or otherwise. In all cases, it is the responsibility of the users to determine the applicability of such information or the suitability of any products for their own purpose.



UNISTEP SOAP

Unistep Soap is wood floor soap for 1 component oiled floors, Re-oiling property, refreshes the oiled surface. Makes 1 component oiled floors more resistant to wear and prolongs the intervals between maintenance procedures. Recommended maintenance after every 5th cleaning with Unistep Cleaner. Available in white and natural.

PREPARATION

The floor must be free from contamination and dust. Clean with Unistep Cleaner.

APPLICATION

Dilute Unistep Soap with cold water (max 20°C) as per directions below. Wipe the floor with a clean, damp mop. Do not rinse the floor with water afterwards. After treating an oiled floor with Soap the surface may appear matt. It can easily be polished up with a dry cotton cloth.

NOTE! Never pour water directly onto oiled wooden floors, instead use a damp cloth or floor mop and remove excess water immediately.

FREQUENCY OF USE

To maintain the look and the protective properties of floor oil, we recommend using Unistep Soap instead of Unistep Cleaner every fifth clean. If treatment with Unistep Soap no longer gives the desired effect, the floor can be treated with Unistep Care Oil.

CLEANING

Clean tools with warm water.

HEALTH AND ENVIRONMENT

Use the normal due care when handling chemical products. Ensure good ventilation. Use protective goggles and gloves if there is any risk of splash-ing. If the product comes into contact with your skin, wash it off with soap and water. If the product gets into your eyes, rinse with a generous amount of water. For further information see Safety Data Sheet.

TECHNICAL DATA

Contents: Saponified pine wood oil, solvent free

pH: Concentrate 9-9,5

Diluted solution: 8,5-9

Dilution: 1:20 Refresher to cold water (<20°C) (50ml Refresher to 1L of water)

Storage: Best before 5 years at 5 to 25°C in unopened package. Protect from frost. Keep out of reach for children.

Package: 1 litre plastic cans

This Unistep Product Sheet is intended for advice only. The figures apply to normal conditions, which may vary due to means of application, temperature etc. We retain the right to make changes and amendments without prior notice. A safety data sheet is available for professional users on request. Keep out of the reach of children.

The information and recommendations in this data sheet are guidelines for application and are not to be construed as a guarantee. In all cases it is the responsibility of the user to determine if the product is suitable for the purpose, and complete a successful application. Unistep can only guarantee the delivered product. If the user is in doubt we would recommend a preliminary onsite test. Please ensure you have read and understood all information on the labels and in the safety data sheets before using this product. This data sheet replaces all previous versions.